



## ATEX hot air dryer

The complete solution for drying

SWISS  
MADE 



### Technical characteristics

- Width : 850 mm
- Depth : 1050 mm
- Working height : 1000 mm
- Overall height : 1500 mm
  
- ATEX marking Ex II 3G IIB T3 en standard
- Rotational speed 20 to 1000 rpm or static
- Temperature Adjustable up to 200°C
- Weight of the load Up to 30 kg ± balanced
- Power 3.5 kW
- Energies 400 VAC and compressed air
- Circulation de l'air By 2 integrated turbines
- Evacuation de l'air On a central vacuum
- Transfer of revenues By USB stick

### Programmable recipe settings

- Rotational speed
- Direction of rotation
- Acceleration/deceleration
- Vertical stirring
- Drying temperature
- Internal air circulation with or without recirculation
- Infinite sequence ability

### Benefits

- ATEX safety
- Static or dynamic drying
- Drum suitable for existing baskets and accessories
- Assisted opening and closing of the lid; ergonomics and safety
- Drying with air recirculation to save time and energy
- Fast and excellent drying quality thanks to the air circulation turbines
- No impact on the parts during the entire drying cycle
- 15" touch-friendly user interface
- Servo motor controlled rotation and acceleration
- Vertical agitation to loosen parts between drying phases
- Energy saving module, automatic preheating



Non-contractual photos and specifications

